

Half-Wave Gas and Mercury-Vapor Rectifier

GENERAL DATA

Electrical:^a


Filament, Coated:

Voltage (AC)	2.5	volts
Current at 2.5 volts.	18 ± 2	amp
Minimum heating time prior to tube conduction.	60	sec
Typical Anode Starting Voltage.	20	volts
Peak Tube Voltage Drop at anode amperes = 20.	9	volts

Mechanical:

Operating Position.	Vertical, base down
Maximum Overall Length.	9 1/2"
Maximum Diameter.	2 1/16"
Weight (Approx.).	6 oz
Bulb.	T16
Cap.	Medium (JEDEC No.C1-5)
Socket.	Super-Jumbo 4-Contact
Base.	Medium-Metal-Shell Super-Jumbo 4-Pin
Terminal Diagram:	BOTTOM VIEW

- Pin 1 - No Internal Connection
- Pin 2 - Filament
- Pin 3 - Filament



- Pin 4 - No Internal Connection
- Cap - Anode

Thermal:

Type of Cooling	Convection
Temperature Rise of Condensed Mercury to Equilibrium Above Ambient	
Temperature (Approx.)	30 °C

HALF-WAVE RECTIFIER^a

Maximum and Minimum Ratings, Absolute-Maximum Values:

For power-supply frequency of 60 cps

PEAK INVERSE ANODE VOLTAGE. 1000 max. volts
ANODE CURRENT:

Peak.	77 max.	amp
Average ^b	6.4 max.	amp
Fault.	770 max.	amp
CONDENSED-MERCURY TEMPERATURE RANGE (Operating) ^c	-40 to +100	°C



635/7019

a With circuit returns to filament-transformer center-tap.

b Averaged over any interval of 20 seconds maximum.

c For longest life, the operating condensed-mercury temperature range after warm-up should be kept between +40° and +100° C which corresponds approximately to +10° to +70° C ambient.

